Ottawa Boom Lift License

Ottawa Boom Lift License - In order to operate an aerial boom lift, operators must be licensed through training which can be attained utilizing both classroom sessions and practical training and by obtaining a boom lift license. Instruction must be given with respect to the type of aerial lift which would be used on the job. A License is needed for anybody who operates or works on an aerial boom lift.

Various types of vehicle-mounted aerial devices consist of extensible boom platforms, aerial ladders, vertical towers, articulating boom platforms, and any combination of these types.

When utilizing a boom lift, there are a few basic safety regulations which apply to all boom lifts. Safety of the worker is a main concern whilst they are working within the basket. The worker should at all times wear a body harness and lanyard, attaching it to the basket or boom. Never tie off to an equipment, an adjacent pole or a structure. Workers should stand on the basket floor, and never climb or sit on the basket edge. The load limits of the manufacturer should be adhered to.

Aerial lift operators should be authorized to use the machinery. The operator must be familiar with all the aspects of the device and must have access to the manufacturers instruction manual which should be kept in the lift. Operators are responsible for ensuring that safety procedures are followed in the operation of the lift. A daily test of lift controls should be carried out. Position outriggers and set brakes (if they are utilized) on a stable surface or on pads. If working on a slope, utilize wheel chocks.

Never move an aerial lift truck with an elevated boom while workers are inside the basket. Articulating boom and extensible boom platforms made use of as personnel carriers must have plainly marked, accessible, upper controls. Except in emergency cases, lower controls should not be utilized to override upper controls unless the person within the lift gives permission.

Do not wear tree or pole climbers shall while working from an aerial lift.
Do not alter the insulated part of the aerial lift.
Do inspect the booms to make certain that it is properly cradled and the outriggers are in the stowed position prior to moving.
Make sure that lifts being utilized near or in power lines are di-electrically tested and conform to local regulations.